

## TECHNICAL DATA

<b>Consistency:</b>	paste
<b>Application temperature:</b>	+5°C / +35°C
<b>Specific weight:</b>	1,42 kg/dm <sup>3</sup>
<b>Dosage:</b>	approx 1 % - 2 % in volume or weight
<b>Full curing:</b>	from 4 to 6 hours depending on % of product applied

Values given in this table must not be considered as specifications.

## PRODUCT

**MS BOOSTER F** is a polymerization accelerator to be used with sealants-adhesives based on MS Polymer produced by Fratelli Zucchini S.p.A.

The low viscosity ensures a manual mixing, especially for fluid products in cans.

**MS BOOSTER F** guarantees a faster bond strength thanks to a quick curing in deep almost not bound by humidity conditions.

Particularly suitable to adjust movement soon after application.

The use of **MS BOOSTER F** does not affect MS Polymer sealant characteristics after cure.

## METHOD OF USE

**Application:** **MS BOOSTER F** can be mixed with MS product both by hand and by drill at low speed, to prevent air bubbles.

Here follows table containing workability time (in consideration of the product to be accelerated and ambient conditions)

<b>MS BOOSTER F</b>	<b>Conditions</b>	<b>Workability</b>
[%]	[-]	[min]
1 (val. 50 on syringe fitted)	10°C 50 % u.r.	60 - 70
2 (val. 100 on syringe fitted)	10°C 50 % u.r.	50 - 60
1 (val. 50 on syringe fitted)	35°C 50% u.r..	30 - 40
2 (val. 100 on syringe fitted)	35°C 50% u.r.	20 - 30

Results with MS Roofing

Early in 24-36 hours after cure, the product will show a strong thickness at the surface.

## SAFETY AND HEALTH

See Safety Data Sheet

## STORAGE

36 months from production date.

Store the sealed product in the original packaging in a dry place at a temperature between +5°C and +25°C.

## PACKAGING

Code	Colour	Pack	pcs/box
1004755	white	syringe 100 ml.	15

Other sizes available on request

## Fratelli Zucchini S.p.A.

Via C. Colombo, 6  
44124 Ferrara - Italy

Tel. +39 0532 782711 - info@zucchini.it - www.zucchini.it

AZIENDA CON SISTEMA  
DI GESTIONE QUALITÀ  
CERTIFICATO DA DNV GL  
= ISO 9001 =



All recommendations relating to application and use of Fratelli Zucchini S.p.A. products have been given based on Fratelli Zucchini S.p.A. knowledge and experience, for products appropriately stored, handled and applied in suitable conditions, as indicated in their respective Technical Datasheets. The variability of materials, substrates and conditions of use is such that no warranty of their functionality for a specific application can be deducted from this information, written or verbal recommendation or any other type of suggestion offered. Each user has the responsibility to complete adequate evaluations on the efficacy of the materials offered by Fratelli Zucchini S.p.A., of its products, services, recommendations and suggestions for the specific application need, and must accomplish sufficient testing to ascertain that the final product will be safe and sound for the final intent of the end-user.

Fratelli Zucchini S.p.A., therefore, cannot be fit considered liable for any damage, direct or indirect even for possible wrong, incorrect and unfit use of the products.