

PRIMER 110/PE FOR SCHOCK-PROOF POLYSTYRENE



PRODUCT DESCRIPTION

PRIMER 110/PE is an adhesion promoter of polyurethane adhesives onto polystyrene. It is suitable in the pre-treating polystyrene heels and wedges to be bonded with polyurethane adhesives to uppers or soles.

PROPERTIES

Composition :	synthetic resin in a blend of organic solvents
Colour :	opalescent in solution, lightly white the dried residues
Solvents :	ketones

TECHNICAL DATA

Solid content :	23 - 28%
Viscosity :	600 - 800 mPas (Brookfield spindle 2 speed. 50 at 25°C)

Values valid for product supply specification upon leaving the factory

METHOD OF USE

Application: apply by brush a thin coat of Primer on the parts of the heel and the wedge to be bonded.

Drying time: allow to dry 15 to 20 minutes before spreading the adhesive.

STORAGE STABILITY

18 months if stored in the original container at a temperature range +5°C and +25°C.



Fratelli Zucchini S.p.A.

Via C. Colombo, 6 - 44124 Ferrara - Italy
Tel. + 39 0532 782711 - Fax +39 0532 732121
info@zucchini.it - www.zucchini.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =