# Z.STRIP G ELASTOPLASTIC SEALING TAPE



#### **PRODUCT DESCRIPTION**

**Z.STRIP G** is an elastoplastic compressible and permanently tacky pre-formed sealing strip, ready to apply in a variety of cross sections to customers requirements.

Resistant to sunlight and non-setting the strip produces a durable weatherproof and airproof seal in joints of glass, metal, wood.

## **TYPICAL USES**

- Glazing of doors and windows.
- Installation of curtain walls and prefabricated panels.
- Installation of household appliances into kitchen furniture.
- Sealing in air conditioning systems.
- Metal frames.







#### **PROPERTIES**

Composition:	polyisobuthylene
Availability:	strips in a variety of rectangular or round cross-sections, supplied in reels containing parallel strips protected by two transparent plastic films.
Colour :	grey, black
Adhesion :	good to glass, metals, wood plastics and painted surfaces
Ageing resistance :	very good
Water absorption :	negligible

# **TECHNICAL DATA**

Non-volatile content :	100%
Penetration at 20°-26°C (300 gr. cone):	6,5 - 9,5 mm. *
Resistance to temperature :	-30°C +70°C

<sup>\*</sup> Value valid as product supply specification upon leaving the factory.

## **METHOD OF USE**

**Surface preparation:** the surfaces must be clean, dry and free from dust and grease.

**Application:** no limits. Cross section of strip must outsize slightly the joint one.

**Application of sealing strip:** apply the strip to the substrate, remove the protection on one side pressing lightly, then remove the second protection and assemble the other component of the joint in position.

Owing to its plastic characteristics, the sealing strip should always remain under slight compression.

Application temperature: over + 10°C.

# STORAGE STABILITY

12 months if stored in the original sealed pack, in a dry place, at a temperature under 25° C.



## Fratelli Zucchini S.p.A.

Via C. Colombo, 6 - 44124 Ferrara - Italy Tel. + 39 0532 782711 - Fax +39 0532 732121 info@zucchini.it - www.zucchini.it COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001=