

# Z. Strip SG/72

Plastic sealing tape

### Description

**Z.STRIP SG 72** is a permanently plastic sealing strip, not hardening, tacky, compressible and ready to use in a variety of cross sections, adaptable to any shape or size of joint. Light resistant and water repellent, assures water and air seal to joints between glass, metal and wood.

#### USES

Assembling of household appliances For sealing overlap joints between plates Mechanics For sealing air conditioning systems

#### **CHARACTERISTICS**

Base Material: Packaging	:polyisobuthylene : strips in a variety of rectangular or round cross-sections, supplied in reels protected by a transparent plastic film.
Colours	: grey, black
Adhesion	:good to glass, metals, woods, plastics and painted surfaces
Ageing	: excellent
Water absorption	: negligible

#### **TECHNICAL DATA**

	Non-volatile content	: 100%
•	Penetration at 20 °-26 ℃ (300 g cone)	: 6,5-9 mm.
	Resistance to temperature	: good in the range –20℃+70℃
•	Value valid as product supply specification upon leaving the factory	

#### **METHOD OF USE**

Surface preparation: the surfaces must be clean, dry and free from dust and grease.

Joint dimensions: no limits. Cross section of strip must outsize slightly the joint one.

**Application of sealing strip:** apply the strip to the substrate, pressing lightly, then remove the protection and assemble the other component of the joint in position. Owing to its plastic characteristics, the sealing strip should always remain under slight compression. The sealing strip can be easily moulded and used as filler of any dimension.

Application temperature: over + 10 ℃

## Technical Data Sheet Z. Strip SG/72



#### STORAGE STABILITY

12 months from the date of manufacture if sealant is kept in the original sealed pack at a temperature under 25 °C.

All recommendations relating to application and use of Fratelli Zucchini products have been given in good faith based on Fratelli Zucchini knowledge and experience, and for products appropriately stored, handled and applied in normal conditions, as indicated in their respective Technical Datasheet.

The variability of materials, substrates and conditions of use is such that no warranty of their functionality for a specific application can be deducted from this information, written recommendation or any other type of suggestion offered. Each user has the responsibility to complete adequate evaluations on the efficacy of the materials offered by Fratelli Zucchini, of its

Each user has the responsibility to complete adequate evaluations on the efficacy of the materials offered by Fratelli Zucchini, of its products, services, recommendations and suggestions for the specific application need, and must accomplish sufficient testing to ascertain that the final product will be safe and sound for the final intent of the end-user.

Fratelli Zucchini cannot be considered liable for any damage, direct or indirect derived by a wrong or incorrect use of the products

**F.IIi Zucchini S.r.I.** - Via C. Colombo, 6 Cassana – 44100 Ferrara - Italy Tel. + 39 0532 782734 - Fax +39 0532 732121 - info@zucchini.it - www.zucchini.it revision 12/2004 - pag. 2/2