

Z. Strip R

Elastoplastic preformed sealing tape

Description

Z Strip R is a pre-formed sealing tape, permanently tacky, elastoplastic, ready to apply in a variety of cross-sections. Compressible, non setting, assures water and air seal to joints between glass, metal, plastics and wood.

USES

Glazing of doors and windows
Installation of curtain walls and sandwich panels
Construction of containers, campers and caravans
Overlap joints between plates, acrylic and fibreglass sheets.

CHARACTERISTICS

Base material	: polyisobuthylene
Packaging	: strips in a variety of rectangular or round cross-sections, protected by transparent plastic film or release paper. Available also flat pieces cut at request.
Colour	: grey, black
Adhesion	: good to glass, metal, wood, plastics
Ageing	: very good
Water absorption	: negligible

TECHNICAL DATA

- | | |
|-----------------------------|--------|
| Non-volatile content | : 100% |
|-----------------------------|--------|
- **Penetration at 20°-26°C (300 g. cone)** : 7,5 – 10,5 mm.
 - **Resistance to temperature** : good in the range -30°C+70°C
 - Value valid as product supply specification upon leaving the factory

METHOD OF USE

Surface preparation: the surfaces must be clean, dry and free from dust and grease

Joint dimension: no limits. Cross section of strip must outsize slightly the joint one.

Application : apply the strip to the substrate pressing lightly, remove the protection and assemble the parts. Owing to its elastoplasticity, the sealing strip should always remain under slight compression.

Application temperature: over +10° C

STORAGE STABILITY

12 months from the date of manufacture if sealant is kept in the original sealed pack at a temperature under 25 °C.

All recommendations relating to application and use of Fratelli Zucchini products have been given in good faith based on Fratelli Zucchini knowledge and experience, and for products appropriately stored, handled and applied in normal conditions, as indicated in their respective Technical Datasheet.

The variability of materials, substrates and conditions of use is such that no warranty of their functionality for a specific application can be deducted from this information, written recommendation or any other type of suggestion offered.

Each user has the responsibility to complete adequate evaluations on the efficacy of the materials offered by Fratelli Zucchini, of its products, services, recommendations and suggestions for the specific application need, and must accomplish sufficient testing to ascertain that the final product will be safe and sound for the final intent of the end-user.

Fratelli Zucchini cannot be considered liable for any damage, direct or indirect derived by a wrong or incorrect use of the products