

Z.STRIP SI 42 CARAVAN



Z.STRIP SI 42 is an elastoplastic, compressible and permanently high tacky pre-formed sealing strip, suitable for sealing overlap seams between metals, glass and plastics.



Typical uses

- Sealing between metal or plastic profiles and aluminum or fiberglass caravan wall boards.
- Installation of glasses on metal, plastic and wood frames.
- Metal carpentry.
- Flanged or overlap joints between sheet metals and plastic materials.



Properties

Base material :	polyisobuthylene
Adhesion :	very good to glass, metals and plastics
Ageing resistance :	excellent
Water absorption :	negligible

Availability

Code	Colour	Section	Packaging	Pcs./Carton
1005745	white	20x2	25	8
1005746 *	white	15x2	25	8

* available on request.
Other rectangular or round cross-sections, supplied in reels or flat pieces and grey colour available on request.

Technical data

Non-volatile content :	100%
Penetration at 20°-26°C (300 gr. cone) :	8,0 - 10,0 mm. *
Resistance to temperature :	-30°C / +80°C

* Value valid as product supply specification upon leaving the factory.

Method of use

Surface preparation: the surfaces must be clean and dry.

Joint dimensions: no limits. Cross section of strip must outsize slightly the joint one, to ensure a steady pressure during service.

Application: apply the strip to the substrate pressing lightly then remove the release paper and assemble the second component of the joint in position.

Temperatura di applicazione: superiore a +5°C.

Storage stability

At least 12 months if stored in the original sealed pack, in a dry place, at a temperature under 25° C.



Fratelli Zucchini S.p.A.
Via C. Colombo, 6 - 44124 Ferrara - Italy
Tel. + 39 0532 782711 - Fax +39 0532 732121
info@zucchini.it - www.zucchini.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =