MS SPRAY F FOOTWARE

MS Spray F is a one-part adhesive based on MS PolymerTM which cures with the humidity of the environment and of the bonded substrates. No solvents or isocyanates, not subject to shrinkage after polymerization it develops high bonding strength, permanent elasticity, excellent moisture resistance and adhesion to substrates.

- One component, ready to use without mixing.
- Solventless and isocyanates free.
- Permanent elasticity at temperatures between -40°C and +90°C.
- Neutral reaction, absence of odour.
- Very fast curing.
- Good resistance to ageing and moisture.
- High bonding strength.

Typical uses

MS Spray F is indicated for bonding and sealing covering, like rubber and similar to many substrates, as fabric or synthetic, a previous test is always recommended.

Properties

Base material :	MS Polymer
Consistency :	paste
Colour :	grey
Application temperature : +5° +35°C	
Packaging :	290 ml. cartridge, 5 Kg. pail

Technical data

Specific gravity :	1,4 kg/dm³
Shore A Hardness (DIN 53505) :	35 - 40
100% modulus (DIN 53504) :	0,9 - 1,1 MPa
Tensile strength (DIN 53504) :	2,0 - 2,5 MPa
Elongation at break :	170 - 280 %
Tear resistance (ASTM D 624-73) :	7-8 N/mm
Peel strength 180° (UNI EN 28510/2) :	> 50 N/25mm
Skin forming time :	50 - 70 approx. (20°C/50% R. H.)
Curing speed :	2 - 3 mm a 24 h. (20°C/50% R. H.)

Values given in this table must not be considered as specifications

Method of use

Adhesion and surface preparation: surfaces to bond must be dry, clean and free from dust or loose material, oil or grease that may affect the adhesion.

Application: spray application with suitable gun or systems at multiple lines.

Storage stability

12 months (290 ml. cartridge), 9 months (5 Kg. pail) for the product stored in the original sealed pack at a temperature range from + 5°C to + 25°C.



Fratelli Zucchini S.p.A. Via C. Colombo, 6 - 44124 Ferrara - Italy Tel. + 39 0532 782711 - Fax +39 0532 73:

Tel. + 39 0532 782711 - Fax +39 0532 732121 info@zucchini.it - www.zucchini.it COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = ISO 9001=

All recommendations relating to application and use of Fratelli Zucchini S.p.A. products have been given in good faith based on Fratelli Zucchini S.p.A. knowledge and experience, and for products appropriately stored, handled and applied in normal conditions, as indicated in their respective Technical Datasheet. The variability of materials, substrates and conditions of use is such that no warranty of their functionality for a specific application can be deducted from this information, written recommendations or any other type of suggestion offered. Each user has the responsibility to complete adequate evaluations on the efficacy of the materials offered by Fratelli Zucchini S.p.A., of its products, services, recommendations and suggestions for the specific application need, and must accomplish sufficient testing to ascertain that the final product will be safe and sound for the final intent of the end-user. Fratelli Zucchini S.p.A. cannot be considered liable for any damage, direct or indirect derived by a wrong or incorrect use of the products.

