

PRIMER GX FOR MS SCREEN



Black primer specific for treating glass without ceramic coating. Applied before MS Screen, the product forms a protective film against UV radiation on the bonding surface between the sealant and the glass.

Characteristics

Colour :	black
Packaging :	cod. 1103237 50 gr. glass bottle
	cod. 1103238 1 Kg. plastic bottle

Method of use

Surface preparation: Primer GX must be applied on clean and dry glass, free from dust and grease. Cleaning must be done with a wad soaked in **Pulitore E** (drying time about 10 min.)

Application: the package must be kept well closed until it is used. Do not use **Primer GX** directly from the original package. Being a very fast drying product it is recommended that the necessary quantity for treating a windscreen be poured into a suitable clean glass container or tin and used immediately, closing the original package. For a correct application, completely deep the felt pad included in the package into the **Primer GX** and lay a uniform film on the glass in one pass so as to give the maximum coverage to the surface to be sealed and to obtain its effective protection from UV radiation. After a drying time of at least 20 min., **MS Screen** sealant can be applied. The best results are obtained by applying the sealant within 4 hours from the treating of the glass with **Primer GX**. Therefore, it is advisable not to apply the Primer to surfaces that cannot be sealed within this time.

Coverage: 3-4 m²/lt.

Cautions

Avoid bare hand contact with the surface treated with **Primer GX** as contamination with greasy substances can reduce sealant adhesion.

Storage stability

6 months for the product stored in the original sealed container at a temperature range from + 5°C to + 30°C.