

PASTA PULTRICE

PRODUCT DESCRIPTION AND CHARACTERISTICS

Paste designed for in-line cleaning of pipes, static mixers, and pressing plate extruder nozzles used for the application of sealants. In particular, it is suitable for preparing extruders for the application of **MS polymer**-based sealants by removing in-line other sealants such as Polyurethanes, Silicones, Polysulphides and other high-viscosity pastes.

TECHNICAL DATA

| | |
|---------------------------------|------------------------|
| Consistency: | Pasty |
| Application temperature: | +5°C / +35°C |
| Specific Gravity: | 1,8 kg/dm ³ |

Values given in this table must not be considered as specifications.

METHOD OF USE

Application: PASTA PULTRICE can be applied with special pressing plate extruder systems. Typical pressures of use minimum 3 bar or more depending on the product to be removed

SAFETY AND HEALTH

See Information Sheet.

STORAGE STABILITY

18 months from production date in the original container.
Keep the product in a dry place at a temperature range between +5°C/+25°C.

PACKAGING

| Code | Colour | Packaging | Unit |
|---------|--------|-------------|------|
| 1004121 | white | drum 25 Kg. | - |
| 1004128 | grey | drum 25 Kg. | - |

Product available only on request.



Fratelli Zucchini S.p.A.

Via C. Colombo, 6 Tel. +39 0532 782711 info@zucchini.it
44124 Ferrara - Italy Fax +39 0532 732121 www.zucchini.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

