

DECLARATION OF PERFORMANCE CE

According to Annex III of the Regulation (EU) No 305/2011

MS CERBONDING – DOP N°16 10 5006151 EN

1. Unique identification code of the product-type:

MS CERBONDING – Liquid-applied water impermeable moisture product.

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

All external installations beneath ceramic tiling.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Fratelli Zucchini S.p.A. - Via C. Colombo, 6 – 44124 Ferrara (Italy)

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N.A.

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body Elletipi s.r.l. (NB 1308) performed the determination of the product-type according to EN 14891 on the basis of product testing under system 3 and issued test reports.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N.A.

Fratelli Zucchini S.p.A.

Registered Office and Headquarters

Via C. Colombo, 6 Tel. + 39 0532 782711 info@zucchini.it P.I. IT 00056730385 N. Mecc. Estero:
44124 Ferrara - Italy Fax + 39 0532 732121 www.zucchini.it C.F. 00056730384 FE 00140 - R.E.A. FE n. 13878**DECLARATION OF PERFORMANCE CE**

According to Annex III of the Regulation (EU) No 305/2011

MS CERBONDING – DOP N°16 10 5006151 EN

9. Declared performance

a. **EN 14891:2012: type RM reaction resin liquid-applied water impermeable product.**

Essential characteristics	Performance	Harmonised technical specification
Initial tensile adhesion strength:	≥ 0,5 N/mm ²	EN 14891:2012
Water tightness:	No penetration	
Crack bridging ability at 23°C-50% UR	≥ 0,75 mm	
Crack bridging ability at -5°C:	≥ 0,75 mm	
Crack bridging ability at -20°C:	≥ 0,75 mm	
Durability of initial tensile adhesion against climate/heat ageing action:	≥ 0,5 N/mm ²	
Durability of initial tensile adhesion against water/humidity action:	≥ 0,5 N/mm ²	
Durability of initial tensile adhesion against contact with lime water:	≥ 0,5 N/mm ²	
Durability of initial tensile adhesion against freeze and freeze-thaw cycles:	≥ 0,5 N/mm ²	
Release of chemicals dangerous to the environment and health:	See MSDS	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

N.A.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Ferrara 16/10/2018.

Signed for and on behalf of the manufacturer by
Maurizio Mazzaglia
CEO

