

**Fratelli Zucchini S.p.A.**

**Registered Office and Headquarters**

Via C. Colombo, 6 Tel. + 39 0532 782711 info@zucchini.it P.I. IT 00056730385 N. Mecc. Estero:  
44124 Ferrara - Italy Fax + 39 0532 732121 www.zucchini.it C.F. 00056730384 FE 00140 - R.E.A. FE n. 13878

## DECLARATION OF PERFORMANCE CE

According to Annex III of the Regulation (EU) No 305/2011

# PANTASIL - DOP N° 14 05 5006486

1. Unique identification code of the product-type:

**PANTASIL – PROFESSIONAL ACETIC CURING SILICONE SEALANT.**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: see packaging of the product.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

- EN15651-1: F-EXT-INT-CC sealant for façade for interior and exterior application (intended for use in cold climates).**
- EN15651-2: G-CC sealant used for sealing glazing applications (intended for use in cold climates).**
- EN15651-3: S sealant for joints in sanitary areas.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Fratelli Zucchini S.p.A. - Via C. Colombo, 6 – 44124 Ferrara (Italy)**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N.A.**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3  
System 3 for the reaction to fire**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The notified body SKZ TeConA GmbH (NB01213) performed the determination of the product-type and reaction to fire class according to EN 15651-1, EN 15651-2 and EN 15651-3 on the basis of product testing under system 3 and issued test reports.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**N.A.**

## DECLARATION OF PERFORMANCE CE

According to Annex III of the Regulation (EU) No 305/2011

# PANTASIL - DOP N° 14 05 5006486

### 9. Declared performance

#### a. EN 15651-1: F-EXT-INT-CC CLASS – 25 LM

Conditioning: Method A (according to ISO8340)  
Substrates: Glass without primer  
Aluminum without primer

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire (EN 13501)	Class E	<b>EN 15651-1: 2012</b>
Release of chemicals dangerous to the environment and health	See MSDS	
<b>Water and air tightness</b>		
Resistance to flow (ISO 7390)	≤ 2 mm.	
Loss of volume (ISO 10563)	≤ 10%	
Tensile properties at maintained extension after immersion in water (ISO 10590)	No failure	
Secant tensile modulus at -30°C (ISO 8339)	≤ 0,9 MPa	
Tensile properties at maintained extension at -30°C (ISO 8340)	No failure	
Durability (EN 15651)	Pass	

#### b. EN 15651-2: G-CC CLASS – 25 LM

Conditioning: Method A (according to ISO 8340)  
Substrates: Glass without primer  
Aluminum without primer

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire (EN 13501)	Class E	<b>EN 15651-2: 2012</b>
Release of chemicals dangerous to the environment and health	See MSDS	
<b>Water and air tightness</b>		
Resistance to flow (ISO 7390)	≤ 2 mm.	
Loss of volume (ISO 10563)	≤ 10%	
Adhesion and cohesion properties after exposure to artificial light (ISO 11431 - pre-conditioning method B)	No failure	
Elastic recovery (ISO 7389)	≥ 70%	
Secant tensile modulus at -30°C (ISO 8339)	≤ 0,9 MPa	
Tensile properties at maintained extension at -30°C (ISO 8340)	No failure	
Durability (EN 15651)	Pass	

**Fratelli Zucchini S.p.A.**
**Registered Office and Headquarters**

 Via C. Colombo, 6 Tel. + 39 0532 782711 info@zucchini.it P.I. IT 00056730385 N. Mecc. Estero:  
 44124 Ferrara - Italy Fax + 39 0532 732121 www.zucchini.it C.F. 00056730384 FE 00140 - R.E.A. FE n. 13878

# DECLARATION OF PERFORMANCE CE

According to Annex III of the Regulation (EU) No 305/2011

## PANTASIL - DOP N° 14 05 5006486

**c. EN 15651-3: S CLASS – XS1**

 Conditioning: Method A (according to ISO8340)  
 Substrates: Glass without primer  
 Aluminum without primer

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire (EN 13501)	Class E	<b>EN 15651-3: 2012</b>
Release of chemicals dangerous to the environment and health	See MSDS	
<b>Water and air tightness</b>		
Resistance to flow (ISO 7390)	≤ 2 mm.	
Loss of volume (ISO 10563)	≤ 10%	
Tensile properties at maintained extension after immersion in water (ISO 10590)	No failure	
Evaluation of the action of microorganisms (ISO 846)	1	
Durability	Pass	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

N.A.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Ferrara 02-10-2014.

Signed for and on behalf of the manufacturer by  
 Maurizio Pazzaglia  
 CEO

