Z.PLAST 5080

PRODUCT DESCRIPTION AND CHARACTERISTICS

Z.PLAST 5080 is a pasty solvent based adhesive, black, suitable for bonding rubber and semi rigid PVC to concrete, wood, bituminous conglomerates and metals.

USES

- For bonding rubber and vinyl floorings.
- For fixing cones in road marking.
- For fixing gaskets.





TECHNICAL DATA

Composition:	rubber, resins and fillers in a blend of organic solvents	
Consistency:	high viscosity, pasty	
Mode of setting:	release of solvent	
Colour:	black	
Solvents:	aliphatic hydrocarbons	
Solids content:	50% - 60%	
Solid content (Brookfield spindle 6 speed 2,5 at 20 - 26°C):	100 [.] 000 - 200 [.] 000 mPa.s	

Value valid as product supply specification on leaving factory.

METHOD OF USE

ADHESIVES

Surface preparation: the materials must be dry and clean. Onto vulcanised rubbers best results can be reached by roughing the surface before adhesive application.

Application: apply by a toothed putty knife an even coat of adhesive onto both the surfaces to join.

Drying time: allow to dry 15 minutes so the solvent can evaporate.

Assembly: after drying assembly the parts and press to assure the contact between the adhesive films.

Yield: 1,0 – 1,5 kg/m².

Note: for bonding that do not require high initial strength, **Z.PLAST 5080** can be applied in a single coat and joining the parts when the adhesive is still wet; this method can be used with porous materials, not sensitive to solvent.

SAFETY AND HEALTH

See Safety Data Sheet.

STORAGE STABILITY

12 months in the original sealed pack stored in a dry place at a temperature range +5°C / +25°C.

AVAILABILITY

Code	Packaging	Pcs./box
1102575	tin 4,5 Kg.	4



Fratelli Zucchini S.p.A. Via C. Colombo, 6 44124 Ferrara - Italy Tel. +39 0532 782711 info@zucchini.it www.zucchini.it



All recommendations relating to application and use of Fratelli Zucchini S.p.A. products have been given based on Fratelli Zucchini S.p.A. knowledge and experience, for products appropriately stored, handled and applied in suitable conditions, as indicated in their respective Technical Datasheets. The variability of materials, substrates and conditions of use is such that no warranty of their functionality for a specific application can be deducted from this information, written or verbal recommendation or any other type of suggestion offered. Each user has the responsibility to complete adequate evaluations on the efficacy of the materials offered by Fratelli Zucchini S.p.A., of its products, services, recommendations and suggestions for the specific application need, and must accomplish sufficient testing to ascertain that the final product will be safe and sound for the final intent of the end-user. Fratelli Zucchini S.p.A., therefore, cannot be fit considered liable for any damage, direct or indirect even for possible wrong, incorrect and unfit use of the products.

